

Spec/Model	MFW-10	MFW-12	KDC-10	KDC-12	KDC-15	KLE-10	KLE-12	KMX-10	KMX-12	KMX-15
Power	800	1000	350	400	500	250	300	700	800	1000
Mag. Wgt. (oz)	160	200	130	180	290	55	60	170	270	270
V.C. Size (in.)	2.5	2.5	2.0	2.0	2.5	2.0	2.0	3.0	3.0	4.0
V.C. Imp	4Ω	4Ω	4Ωx2	4Ωx2	4Ωx2	4Ω	4Ω	2Ωx2	2Ωx2	2Ωx2
Fs (Hz)	31.62	29.3	38.6	36.5	29.6	31.3	31.9	35.2	27.39	29.6
Vas (Cu. Ft.)	0.893	1.689	0.65	1.3	3.95	1.05	1.86	0.48	1.45	1.79
Qms	8.2866	9.3983	5.40	4.237	2.243	5.235	2.97	5.27	5.13	4.685
Qes	0.5648	0.6337	0.736	0.667	0.605	0.472	0.638	0.479	0.418	0.484
Qts	0.529	0.5936	0.647	0.576	0.476	0.4325	0.525	0.439	0.3867	0.439
Xmax (in.)	0.39	0.39	0.394	0.394	0.493	0.315	0.315	0.473	0.473	0.748
SPL	89	91	90	91	93	91	92	89	90	92
Box Style	S	S	S/P	S/P	S/P	S/P	S/P	P	P	P
Box Size (S) (Cu.Ft.)	1.0	1.2	0.7	1.0	2.0	0.5	1.0	N/A	N/A	N/A
Box Size (P) (Cu. Ft.)	N/A	N/A	1.75	2.5	4.0	1.6	3.0	1.75	2.4	3.0
Port Size (dia."xL")	N/A	N/A	3x5.25	4x8	4x9.6	3x8.25	3x3	4x11	4x8.5	4x11.25
# of Ports	N/A	N/A	1	1	2	1	1	1	1	2
Tune Freq. (Hz)	N/A	N/A	39	34	34	35	38	40	40	40
Hole Dia. (in.)	9.25	11.0	9.33	11.25	14.125	9.125	11.0	9.33	11.25	14.125
Depth (in.)	3.75/4.25	4.0/4.5	6.3	7.0	8.1	4.6	5.0	6.3	7.0	8.1
Outer Ring (in.)										

Box Styles:

S = Sealed

P = Ported

F = Free Air